

Package ‘RcppTOML’

July 21, 2025

Type Package

Title 'Rcpp' Bindings to Parser for ``Tom's Obvious Markup Language''

Version 0.2.3

Date 2025-03-08

Description The configuration format defined by 'TOML' (which expands to ``Tom's Obvious Markup Language'') specifies an excellent format (described at <https://toml.io/en/>) suitable for both human editing as well as the common uses of a machine-readable format. This package uses 'Rcpp' to connect to the 'toml++' parser written by Mark Gillard to R.

SystemRequirements A C++17 compiler

BugReports <https://github.com/eddelbuettel/rcpptoml/issues>

URL <http://dirk.eddelbuettel.com/code/rcpp.toml.html>

Imports Rcpp (>= 1.0.8)

Depends R (>= 3.3.0)

LinkingTo Rcpp

Suggests tinytest

License GPL (>= 2)

NeedsCompilation yes

Author Dirk Eddelbuettel [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-6419-907X>>),
Mark Gillard [aut] (Author of 'toml++' header library)

Maintainer Dirk Eddelbuettel <edd@debian.org>

Repository CRAN

Date/Publication 2025-03-08 14:30:06 UTC

Contents

RcppTOML-package	2
parseTOML	3

RcppTOML-package

R Access to Parser for TOML (Tom's Obvious Markup Language)

Description

TOML (“Tom’s Obvious Markup Language”) is a configuration file grammar for humans. It is easier to read and edit than the alternatives yet arguably more useful as it is strongly typed: values come back as integer, double, (multiline-) character (strings), boolean or Datetime. Moreover, complex nesting and arrays are supported as well.

Details

At present, a single parsing function `parseTOML` (with convenience aliases `tomlparse` and `parseToml`) is implemented. It returns a list object corresponding to the configuration from the supplied file.

Author(s)

Dirk Eddelbuettel put together the R package. Charles Geigle wrote the `cpptoml` parser. Tom Preston-Werner is the Tom behind TOML.

Maintainer: Dirk Eddelbuettel <edd@debian.org>

References

TOML: <https://toml.io/en/>

Examples

```
library(RcppTOML)

file <- system.file("toml", "example.toml", package="RcppTOML")

toml <- parseTOML(file) # given file, return parsed object

summary(toml)           # really sparse summary method
print(toml)             # print is a wrapper around str()
```

parseTOML	<i>Parse a TOML file</i>
-----------	--------------------------

Description

The function `parseTOML`, also aliased to `tomlparse` and `parseToml`, parse TOML content inout. This is usually a file given by its name, or a character variable with a TOML expression.

Usage

```
parseTOML(input, verbose = FALSE, fromFile = TRUE, includize = FALSE,  
          escape = TRUE)
```

```
tomlparse(...)
```

```
parseToml(...)
```

```
## S3 method for class 'toml'
```

```
print(x, ...)
```

```
## S3 method for class 'toml'
```

```
summary(object, ...)
```

Arguments

<code>input</code>	[character] TOML input, either as chracter value or path to TOML file
<code>verbose</code>	[logical] Optional verbosity flag, no current effect
<code>fromFile</code>	[logical] Optional with default value ‘TRUE’ indicating parsing from file
<code>includize</code>	[logical] Optional legacy option, no current effect
<code>escape</code>	[logical] Optional boolean whether strings should be escaped, defaults to ‘TRUE’
<code>...</code>	Used for aliased function and S3 methods
<code>x</code>	Used for S3 method
<code>object</code>	Used for S3 method

Details

This implementation uses the ‘tomlplusplus’ library by Mark Gillar (see <https://github.com/marzer/tomlplusplus>) which is TOML 1.0 compliant. In earlier work the package used the ‘cpp-toml’ library by Chase Geigle (see <https://github.com/skystrike/cpptoml> for which development ceased once TOML 0.5.0 parity was reached.

Value

A list object with the parsed content as an S3 object of class ‘toml’

Index

* **package**

RcppTOML-package, [2](#)

parseTOML, [3](#)

parseToml (parseTOML), [3](#)

print.toml (parseTOML), [3](#)

RcppTOML (RcppTOML-package), [2](#)

RcppTOML-package, [2](#)

summary.toml (parseTOML), [3](#)

tomlparse (parseTOML), [3](#)