

Package ‘SecretsProvider’

July 21, 2025

Type Package

Title Save and Retrieve Name-Value Pairs to and from a File

Version 1.0.0

Date 2025-03-07

Maintainer Koen Greuell <vlic@lifewatch.eu>

Description Facilitates secret management by storing credentials in a dedicated file,
keeping them out of your code base.
The secrets are stored without encryption.
This package is compatible with secrets stored by the 'SecretsProvider' 'Python' package <<https://pypi.org/project/SecretsProvider/>>.

License Apache License (== 2.0)

Suggests testthat (>= 3.0.0), getPass

RoxygenNote 7.3.2

Config/testthat/edition 3

NeedsCompilation no

Author Koen Greuell [aut, cre]

Repository CRAN

Date/Publication 2025-04-02 17:20:05 UTC

Contents

SecretsProvider-package	2
Index	3

SecretsProvider-package*Save and Retrieve Name-Value Pairs to and from a File*

Description

Facilitates secret management by storing credentials in a dedicated file, keeping them out of your code base. The secrets are stored without encryption. This package is compatible with secrets stored by the 'SecretsProvider' 'Python' package <<https://pypi.org/project/SecretsProvider/>>.

Details

Arguments:

secret_file_path Path to the file where secrets are stored. Defaults to ".env".

input_func Function to get input from the user. Defaults to getPass::getPass

Methods:

set_secret(secret_name): Retrieves Saves a secret If there is already a secret with the name given. Entering a new value will overwrite the existing secret.

get_secret(secret_name): Retrieves secret If this secret does not exist, it prompts the user to enter a secret and stores that.

remove_secret(secret_name): Remove a secret

Author(s)

Koen Greuell

Maintainer: Koen Greuell

Examples

```
# Create a SecretsProvider object
secretsProvider <- SecretsProvider(secret_file_path = tempfile(),
                                   input_func = function(prompt) { "mock_input"})

# Set a secret
secretsProvider$set_secret("Data_source_API_key")

# Get a secret
api_key <- secretsProvider$get_secret("Data_source_API_key")

# Remove a secret
secretsProvider$remove_secret("Data_source_API_key")
```

Index

SecretsProvider
 (SecretsProvider-package), [2](#)
SecretsProvider-package, [2](#)