

Package ‘TriDimRegression’

July 22, 2025

Title Bayesian Statistics for 2D/3D Transformations

Version 1.0.2

Description Fits 2D and 3D geometric transformations via 'Stan' probabilistic programming engine (Stan Development Team (2021) <<https://mc-stan.org>>). Returns posterior distribution for individual parameters of the fitted distribution. Allows for computation of LOO and WAIC information criteria (Vehtari A, Gelman A, Gabry J (2017) <[doi:10.1007/s11222-016-9696-4](https://doi.org/10.1007/s11222-016-9696-4)>) as well as Bayesian R-squared (Gelman A, Goodrich B, Gabry J, and Vehtari A (2018) <[doi:10.1080/00031305.2018.1549100](https://doi.org/10.1080/00031305.2018.1549100)>).

License GPL-3

URL <https://github.com/alexander-pastukhov/tridim-regression>,
<https://alexander-pastukhov.github.io/tridim-regression/>

BugReports <https://github.com/alexander-pastukhov/tridim-regression/issues>

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

VignetteBuilder knitr

Biarch true

Depends R (>= 4.3.0), loo

Imports methods, Rcpp (>= 0.12.0), rstan (>= 2.26.0), dplyr, future,
glue, purrr, tidyr, Formula, bayesplot

LinkingTo BH (>= 1.66.0), Rcpp (>= 0.12.0), RcppEigen (>= 0.3.3.3.0),
RcppParallel (>= 5.0.1), rstan (>= 2.26.0), StanHeaders (>= 2.26.0)

SystemRequirements GNU make

Suggests testthat, knitr, rmarkdown, ggplot2

NeedsCompilation yes

Author Alexander (Sasha) Pastukhov [aut, cre] (ORCID:
<https://orcid.org/0000-0002-8738-8591>),
 Claus-Christian Carbon [aut] (ORCID:
<https://orcid.org/0000-0002-3446-9347>)

Maintainer Alexander (Sasha) Pastukhov <pastukhov.alexander@gmail.com>

Repository CRAN

Date/Publication 2023-09-13 14:10:03 UTC

Contents

TriDimRegression-package	3
CarbonExample1Data	4
CarbonExample2Data	5
CarbonExample3Data	5
coef.tridim_transformation	6
EyegazeData	7
Face3D_M010	7
Face3D_M101	8
Face3D_M244	8
Face3D_M92	9
Face3D_W070	9
Face3D_W097	10
Face3D_W182	10
Face3D_W243	11
fit_transformation	11
fit_transformation_df	13
FriedmanKohlerData1	14
FriedmanKohlerData2	15
is.tridim_transformation	15
loo.tridim_transformation	16
NakayaData	16
plot.tridim_transformation	17
predict.tridim_transformation	18
print.tridim_transformation	19
R2	19
summary.tridim_transformation	20
tridim_transformation-class	21
waic.tridim_transformation	21

Index

23

TriDimRegression-package

The 'TriDimRegression' package.

Description

Fits 2D and 3D geometric transformations. Provides posterior via Stan. Includes computation of LOO and WAIC information criteria, R-squared.

To fit transformation, call the main function either via a formula that specifies dependent and independent variables with the data table or by supplying two tables one containing all independent variables and one containing all dependent variables.

For the 2D data, you can fit "translation" (2 parameters for translation only), "euclidean" (4 parameters: 2 for translation, 1 for scaling, and 1 for rotation), "affine" (6 parameters: 2 for translation and 4 that jointly describe scaling, rotation and sheer), or "projective" (8 parameters: affine plus 2 additional parameters to account for projection). For 3D data, you can fit "translation" (3 for translation only), "euclidean_x", "euclidean_y", "euclidean_z" (5 parameters: 3 for translation scale, 1 for rotation, and 1 for scaling), "affine" (12 parameters: 3 for translation and 9 to account for scaling, rotation, and sheer), and "projective" (15 parameters: affine plus 3 additional parameters to account for projection). transformations. For details on transformation matrices and computation of scale and rotation parameters please see `vignette("transformation_matrices", package = "TriDimRegression")`

Once the data is fitted, you can extract the transformation coefficients via `coef` function and the matrix itself via `transformation_matrix`. Predicted data, either based on the original data or on the new data, can be generated via `predict`. Bayesian R-squared can be computed with or without adjustment via `R2` function. In all three cases, you have choice between summary (mean + specified quantiles) or full posterior samples. `loo` and `waic` provide corresponding measures that can be used for comparison via `loo::loo_compare()` function.

Author(s)

Maintainer: Alexander (Sasha) Pastukhov <pastukhov.alexander@gmail.com> ([ORCID](#))

Authors:

- Claus-Christian Carbon <ccc@experimental-psychology.com> ([ORCID](#))

References

Stan Development Team (2020). RStan: the R interface to Stan. R package version 2.19.3. <https://mc-stan.org>

See Also

```
fit_transformation fit_transformation_df tridim_transformation vignette("transformation_matrices",
package = "TriDimRegression") vignette("calibration", package = "TriDimRegression")
vignette("comparing_faces", package = "TriDimRegression")
```

Examples

```
# Fitting via formula
euc2 <- fit_transformation(depV1 + depV2 ~ indepV1 + indepV2,
                           NakayaData, 'euclidean')
aff2 <- fit_transformation(depV1 + depV2 ~ indepV1 + indepV2,
                           NakayaData, 'affine')
prj2 <- fit_transformation(depV1 + depV2 ~ indepV1 + indepV2,
                           NakayaData, 'projective')

# summary of transformation coefficients
coef(euc2)

# statistical comparison via WAIC criterion
loo::loo_compare(waic(euc2), waic(aff2), waic(prj2))

# Fitting via two tables
euc2 <- fit_transformation_df(NakayaData[, 1:2], NakayaData[, 3:4],
                              'euclidean')
tr3 <- fit_transformation_df(Face3D_W070, Face3D_W097, transformation = 'translation')
```

CarbonExample1Data	<i>Carbon, C. C. (2013), data set #1</i>
--------------------	--

Description

Example 1 from the domain of aesthetics to show how the method can be utilized for assessing the similarity of two portrayed persons, actually the Mona Lisa in the world famous Louvre version and the only recently re-discovered Prado version.

Usage

```
CarbonExample1Data
```

Format

A data frame with 36 observations on the following 4 variables:

depV1, depV2 numeric vectors, dependent variables

indepV1, indepV2 numeric vectors, independent variables

Source

[doi:10.18637/jss.v052.c01](https://doi.org/10.18637/jss.v052.c01)

CarbonExample2Data	<i>Carbon, C. C. (2013), data set #2</i>
--------------------	--

Description

Example 2 originates from the area of geography and inspects the accuracy of different maps of the city of Paris which were created over the last 350 years as compared to a recent map.

Usage

CarbonExample2Data

Format

A data frame with 13 observations on the following 4 variables:

depV1, depV2 numeric vectors, dependent variables

indepV1, indepV2 numeric vectors, independent variables

Source

[doi:10.18637/jss.v052.c01](https://doi.org/10.18637/jss.v052.c01)

CarbonExample3Data	<i>Carbon, C. C. (2013), data set #3</i>
--------------------	--

Description

Example 3 focuses on demonstrating how good a cognitive map recalculated from averaged cognitive distance data fits with a related real map.

Usage

CarbonExample3Data

Format

A data frame with 10 observations on the following 4 variables:

depV1, depV2 numeric vectors, dependent variables

indepV1, indepV2 numeric vectors, independent variables

Source

[doi:10.18637/jss.v052.c01](https://doi.org/10.18637/jss.v052.c01)

```
coef.tridim_transformation
```

Posterior distributions for transformation coefficients in full or summarized form.

Description

Posterior distributions for transformation coefficients in full or summarized form.

Usage

```
## S3 method for class 'tridim_transformation'
coef(
  object,
  summary = TRUE,
  probs = c(0.055, 0.945),
  convert_euclidean = FALSE,
  ...
)
```

Arguments

object	An object of class tridim_transformation .
summary	Whether summary statistics should be returned instead of raw sample values. Defaults to TRUE
probs	The percentiles used to compute summary, defaults to 89% credible interval.
convert_euclidean	Whether to convert matrix coefficients to scale(phi) and rotation(theta). Defaults to FALSE.
...	Unused

Value

If summary=FALSE, a list with matrix iterations $N \times \text{dimensions}$ for each variable. If summary=TRUE, a data.frame with columns "dvindex" with mean for each dependent variable plus optional quantiles columns with names "dvindex_quantile".

Examples

```
euc2 <- fit_transformation(depV1+depV2~indepV1+indepV2,
  data = NakayaData,
  transformation = 'euclidean')

# full posterior distribution
transform_posterior <- coef(euc2, summary=FALSE)

# coefficients' summary with 89% CI
```

```
coef(euc2)

# scale and rotation coefficients
coef(euc2, convert_euclidean=TRUE)
```

EyegazeData

Eye gaze calibration data

Description

A dataset containing a monocular eye gaze recording with calibration sequence. Courtesy of **Bamberger Baby Institut: BamBI**.

Usage

```
EyegazeData
```

Format

A data frame with 365 rows and 6 variables:

time sample timestamp, in milliseconds

x, y recorded gaze, in internal eye tracker units

target_x, target_y location of the calibration target on the screen, in pixels

target index of the target within the sequence

Source

<https://www.uni-bamberg.de/entwicklungspsychologie/transfer/babyforschung-bambi/>.

Face3D_M010

Face landmarks, male, #010

Description

Face landmarks, male, #010

Usage

```
Face3D_M010
```

Format

A data frame with 64 landmarks on the following 3 variables:

x, y, z numeric vectors, coordinates of face landmarks

Source

Carbon, C. C. (2012). The Bamberg DADA Face Database (BaDADA). A standardized high quality Face Database with faces of Different Affective states from Different Angles. Unpublished databank. University of Bamberg, Bamberg.

Face3D_M101	<i>Face landmarks, male, #101</i>
-------------	-----------------------------------

Description

Face landmarks, male, #101

Usage

Face3D_M101

Format

A data frame with 64 landmarks on the following 3 variables:

x, y, z numeric vectors, coordinates of face landmarks

Source

Carbon, C. C. (2012). The Bamberg DADA Face Database (BaDADA). A standardized high quality Face Database with faces of Different Affective states from Different Angles. Unpublished databank. University of Bamberg, Bamberg.

Face3D_M244	<i>Face landmarks, male, #244</i>
-------------	-----------------------------------

Description

Face landmarks, male, #244

Usage

Face3D_M244

Format

A data frame with 64 landmarks on the following 3 variables:

x, y, z numeric vectors, coordinates of face landmarks

Source

Carbon, C. C. (2012). The Bamberg DADA Face Database (BaDADA). A standardized high quality Face Database with faces of Different Affective states from Different Angles. Unpublished databank. University of Bamberg, Bamberg.

Face3D_M92*Face landmarks, male, #092*

Description

Face landmarks, male, #092

Usage

Face3D_M92

Format

A data frame with 64 landmarks on the following 3 variables:

x, y, z numeric vectors, coordinates of face landmarks

Source

Carbon, C. C. (2012). The Bamberg DADA Face Database (BaDADA). A standardized high quality Face Database with faces of Different Affective states from Different Angles. Unpublished databank. University of Bamberg, Bamberg.

Face3D_W070*Face landmarks, female, #070*

Description

Face landmarks, female, #070

Usage

Face3D_W070

Format

A data frame with 64 landmarks on the following 3 variables:

x, y, z numeric vectors, coordinates of face landmarks

Source

Carbon, C. C. (2012). The Bamberg DADA Face Database (BaDADA). A standardized high quality Face Database with faces of Different Affective states from Different Angles. Unpublished databank. University of Bamberg, Bamberg.

Face3D_W097	<i>Face landmarks, female, #097</i>
-------------	-------------------------------------

Description

Face landmarks, female, #097

Usage

Face3D_W097

Format

A data frame with 64 landmarks on the following 3 variables:

x, y, z numeric vectors, coordinates of face landmarks

Source

Carbon, C. C. (2012). The Bamberg DADA Face Database (BaDADA). A standardized high quality Face Database with faces of Different Affective states from Different Angles. Unpublished databank. University of Bamberg, Bamberg.

Face3D_W182	<i>Face landmarks, female, #182</i>
-------------	-------------------------------------

Description

Face landmarks, female, #182

Usage

Face3D_W182

Format

A data frame with 64 landmarks on the following 3 variables:

x, y, z numeric vectors, coordinates of face landmarks

Source

Carbon, C. C. (2012). The Bamberg DADA Face Database (BaDADA). A standardized high quality Face Database with faces of Different Affective states from Different Angles. Unpublished databank. University of Bamberg, Bamberg.

Face3D_W243

*Face landmarks, female, #243***Description**

Face landmarks, female, #243

Usage

Face3D_W243

Format

A data frame with 64 landmarks on the following 3 variables:

x, y, z numeric vectors, coordinates of face landmarks

Source

Carbon, C. C. (2012). The Bamberg DADA Face Database (BaDADA). A standardized high quality Face Database with faces of Different Affective states from Different Angles. Unpublished databank. University of Bamberg, Bamberg.

fit_transformation

*Fitting Bidimensional or Tridimensional Regression / Geometric Transformation Models via Formula.***Description**

Fits Bidimensional or Tridimensional regression / geometric transformation models using Stan engine. The formula described dependent and independent numeric variables in the data. See also [fit_transformation_df](#).

For the 2D data, you can fit "translation" (2 parameters for translation only), "euclidean" (4 parameters: 2 for translation, 1 for scaling, and 1 for rotation), "affine" (6 parameters: 2 for translation and 4 that jointly describe scaling, rotation and sheer), or "projective" (8 parameters: affine plus 2 additional parameters to account for projection).

For 3D data, you can fit "translation" (3 for translation only), "euclidean_x", "euclidean_y", "euclidean_z" (5 parameters: 3 for translation scale, 1 for rotation, and 1 for scaling), "affine" (12 parameters: 3 for translation and 9 to account for scaling, rotation, and sheer), and "projective" (15 parameters: affine plus 3 additional parameters to account for projection). transformations.

For details on transformation matrices and computation of scale and rotation parameters please see `vignette("transformation_matrices", package = "TriDimRegression")`

Usage

```
## S3 method for class 'formula'
fit_transformation(
  formula,
  data,
  transformation,
  priors = NULL,
  chains = 1,
  cores = NULL,
  ...
)
```

Arguments

formula	a symbolic description of the model to be fitted in the format $X_{dep} + Y_{dep} \sim X_{ind} + Y_{ind}$, where X_{dep} and Y_{dep} are dependent and X_{ind} and Y_{ind} are independent variables
data	a data frame containing variables for the model.
transformation	the transformation to be used: "translation" (both 2D and 3D), "euclidean" (2D), "euclidean_x", "euclidean_y", "euclidean_z" (3D, rotation about, respectively, x, y, and z axis), "affine" (2D and 3D), or "projective" (2D and 3D).
priors	named list of parameters for prior distributions of parameters a (translation, normal distribution), b (all other parameters, normal distribution), and sigma (residual variance, exponential). E.g., <code>list("a" = c(0, 10), "b" = c(0, 1), "sigma" = 1)</code> . Default priors are <code>"a" = c(0, max_absolute_difference_in_means(d, iv)) / 2</code> , <code>"b" = c(0, max_absolute_difference_in_means(d, iv)) / 2</code> , <code>"sigma" = 1 * sd(dv)</code> .
chains	Number of chains for sampling.
cores	Number of CPU cores to use for sampling. If omitted, all available cores are used.
...	Additional arguments passed to sampling function.

Value

A [tridim_transformation](#) object

See Also

[fit_transformation_df](#)

Examples

```
# Geometric transformations of 2D data
euc2 <- fit_transformation(depV1 + depV2 ~ indepV1 + indepV2,
                           NakayaData, 'euclidean')
aff2 <- fit_transformation(depV1 + depV2 ~ indepV1 + indepV2,
```

```

                                NakayaData, 'affine')
prj2 <- fit_transformation(depV1 + depV2 ~ indepV1 + indepV2,
                          NakayaData, 'projective')

# summary of transformation coefficients
coef(euc2)

# statistical comparison via WAIC criterion
loo::loo_compare(waic(euc2), waic(aff2), waic(prj2))

```

fit_transformation_df *Fitting Bidimensional or Tridimensional Regression / Geometric Transformation Models via Two Tables.*

Description

Fits Bidimensional or Tridimensional regression / geometric transformation models using Stan engine. Two sets of coordinates are supplied via `iv` (for an independent variable) and `dv` (for the dependent one). The two tables must have the same dimensions (both $N \times 2$ or $N \times 3$).

For the 2D data, you can fit "translation" (2 for translation only), "euclidean" (4 parameters: 2 for translation, 1 for scaling, and 1 for rotation), "affine" (6 parameters: 2 for translation and 4 that jointly describe scaling, rotation and sheer), or "projective" (8 parameters: affine plus 2 additional parameters to account for projection).

For 3D data, you can fit "translation" (3 for translation only), "euclidean_x", "euclidean_y", "euclidean_z" (5 parameters: 3 for translation scale, 1 for rotation, and 1 for scaling), "affine" (12 parameters: 3 for translation and 9 to account for scaling, rotation, and sheer), and "projective" (15 parameters: affine plus 3 additional parameters to account for projection). transformations.

For details on transformation matrices and computation of scale and rotation parameters please see `vignette("transformation_matrices", package = "TriDimRegression")`

Usage

```

fit_transformation_df(
  iv,
  dv,
  transformation,
  priors = NULL,
  chains = 1,
  cores = NULL,
  ...
)

```

Arguments

<code>iv</code>	a data frame containing independent variable, must by numeric only, $N \times 2$ or $N \times 3$.
<code>dv</code>	a data frame containing dependent variable, must by numeric only, $N \times 2$ or $N \times 3$.

transformation	the transformation to be used: "translation" (both 2D and 3D), "euclidean" (2D), "euclidean_x", "euclidean_y", "euclidean_z" (3D, rotation about, respectively, x, y, and z axis), "affine" (2D and 3D), or "projective" (2D and 3D).
priors	named list of parameters for prior distributions of parameters a (translation, normal distribution), b (all other parameters, normal distribution), and sigma (residual variance, exponential). E.g., <code>list("a" = c(0, 10), "b" = c(0, 1), "sigma" = 1)</code> . Default priors are <code>"a" = c(0, max_absolute_difference_in_means(d, iv)) / 2)</code> , <code>"b" = c(0, max_absolute_difference_in_means(d, iv)) / 2)</code> , <code>"sigma" = 1 * sd(dv)</code> .
chains	Number of chains for sampling.
cores	Number of CPU cores to use for sampling. If omitted, all available cores are used.
...	Additional arguments passed to sampling function.

Value

A [tridim_transformation](#) object

See Also

[fit_transformation](#)

Examples

```
# Geometric transformations of 2D data
euc2 <- fit_transformation_df(NakayaData[, 1:2], NakayaData[, 3:4], 'euclidean')
tr3 <- fit_transformation_df(Face3D_W070, Face3D_W097, transformation = 'translation')
```

FriedmanKohlerData1 *Friedman & Kohler (2003), data set #1*

Description

Data from Friedman, A., & Kohler, B. (2003). Bidimensional regression: Assessing the configurational similarity and accuracy of cognitive maps and other two-dimensional data sets. *Psychological Methods*, 8(4), 468-491. DOI: 10.1037/1082-989X.8.4.468

Usage

```
FriedmanKohlerData1
```

Format

A data frame with 4 observations on the following 4 variables:

depV1, depV2 numeric vectors, dependent variables

indepV1, indepV2 numeric vectors, independent variables

Source

[doi:10.1037/1082989X.8.4.468](https://doi.org/10.1037/1082989X.8.4.468)

FriedmanKohlerData2	<i>Friedman & Kohler (2003), data set #2</i>
---------------------	--

Description

Data from Friedman, A., & Kohler, B. (2003). Bidimensional regression: Assessing the configural similarity and accuracy of cognitive maps and other two-dimensional data sets. *Psychological Methods*, 8(4), 468-491. DOI: 10.1037/1082-989X.8.4.468

Usage

```
FriedmanKohlerData2
```

Format

A data frame with 4 observations on the following 4 variables:

depV1, depV2 numeric vectors, dependent variables

indepV1, indepV2 numeric vectors, independent variables

Source

[doi:10.1037/1082989X.8.4.468](https://doi.org/10.1037/1082989X.8.4.468)

is.tridim_transformation	<i>Checks if argument is a tridim_transformation object</i>
--------------------------	---

Description

Checks if argument is a tridim_transformation object

Usage

```
is.tridim_transformation(x)
```

Arguments

x	An R object
---	-------------

Value

Logical

loo.tridim_transformation	<i>Computes an efficient approximate leave-one-out cross-validation via loo library. It can be used for a model comparison via loo::loo_compare() function.</i>
---------------------------	---

Description

Computes an efficient approximate leave-one-out cross-validation via loo library. It can be used for a model comparison via loo::loo_compare() function.

Usage

```
## S3 method for class 'tridim_transformation'  
loo(x, ...)
```

Arguments

x	A tridim_transformation object
...	unused

Value

A named list, see [loo::loo\(\)](#) for details.

Examples

```
euc2 <- fit_transformation(depV1+depV2~indepV1+indepV2,  
  NakayaData, transformation = 'euclidean')  
aff2 <- fit_transformation(depV1+depV2~indepV1+indepV2,  
  NakayaData, transformation = 'affine')  
loo::loo_compare(loo(euc2), loo(aff2))
```

NakayaData	<i>Nakaya (1997)</i>
------------	----------------------

Description

Nakaya, T. (1997) Statistical inferences in bidimensional regression models. Geographical Analysis, 29(2), 169-186.

Usage

```
NakayaData
```


Format

A data frame with 19 observations on the following 4 variables:

depV1, depV2 numeric vectors, dependent variables

indepV1, indepV2 numeric vectors, independent variables

Source

[doi:10.1111/j.15384632.1997.tb00954.x](https://doi.org/10.1111/j.15384632.1997.tb00954.x)

plot.tridim_transformation

*Posterior interval plots for key parameters. Uses
bayesplot::mcmc_intervals.*

Description

Posterior interval plots for key parameters. Uses bayesplot::mcmc_intervals.

Usage

```
## S3 method for class 'tridim_transformation'
plot(x, convert_euclidean = FALSE, ...)
```

Arguments

x A [tridim_transformation](#) object

convert_euclidean Whether to convert matrix coefficients to scale(phi) and rotation(theta). Defaults to FALSE.

... Extra parameters to be passed to [bayesplot::mcmc_intervals\(\)](#)

Value

A ggplot object produced by [bayesplot::mcmc_intervals\(\)](#)

Examples

```
euc2 <- fit_transformation(depV1+depV2~indepV1+indepV2,
                           data = NakayaData,
                           transformation = 'euclidean')

plot(euc2)

# same but for converted coefficients
plot(euc2, convert_euclidean=TRUE)
```

```
predict.tridim_transformation
```

Computes posterior samples for the posterior predictive distribution.

Description

Predicted values based on the bi/tridimensional regression model object.

Usage

```
## S3 method for class 'tridim_transformation'
predict(object, newdata = NULL, summary = TRUE, probs = NULL, ...)
```

Arguments

object	An object of class tridim_transformation
newdata	An optional two column data frame with independent variables. If omitted, the fitted values are used.
summary	Whether summary statistics should be returned instead of raw sample values. Defaults to TRUE
probs	The percentiles used to compute summary, defaults to NULL (no CI).
...	Unused

Value

If summary=FALSE, a numeric matrix iterationsN x observationsN x variablesN. If summary=TRUE, a data.frame with columns "dvindex" with mean for each dependent variable plus optional quantiles columns with names "dvindex_quantile".

See Also

[fit_transformation](#)

Examples

```
euc2 <- fit_transformation(depV1+depV2~indepV1+indepV2,
  NakayaData, transformation = 'euclidean')

# prediction summary
predictions <- predict(euc2)

# full posterior prediction samples
predictions <- predict(euc2, summary=FALSE)
```

```
print.tridim_transformation
```

Prints out tridim_transformation object

Description

Prints out tridim_transformation object

Usage

```
## S3 method for class 'tridim_transformation'
print(x, ...)
```

Arguments

x	A tridim_transformation object
...	Unused

Value

Nothing, console output only.

Examples

```
euc2 <- fit_transformation(depV1+depV2~indepV1+indepV2,
                           data = NakayaData,
                           transformation = 'euclidean')

euc2
```

R2	<i>Computes R-squared using Bayesian R-squared approach. For detail refer to: Andrew Gelman, Ben Goodrich, Jonah Gabry, and Aki Vehtari (2018). R-squared for Bayesian regression models. The American Statistician, doi:10.1080/00031305.2018.1549100.</i>
----	---

Description

Computes R-squared using Bayesian R-squared approach. For detail refer to: Andrew Gelman, Ben Goodrich, Jonah Gabry, and Aki Vehtari (2018). R-squared for Bayesian regression models. The American Statistician, doi:10.1080/00031305.2018.1549100.

Usage

```
## S3 method for class 'tridim_transformation'
R2(object, summary = TRUE, probs = c(0.055, 0.945), ...)
```

Arguments

object	An object of class tridim_transformation
summary	Whether summary statistics should be returned instead of raw sample values. Defaults to TRUE
probs	The percentiles used to compute summary, defaults to 89% credible interval.
...	Unused.

Value

vector of values or a data.frame with summary

Examples

```
euc2 <- fit_transformation(depV1+depV2~indepV1+indepV2,
  NakayaData, transformation = 'euclidean')
R2(euc2)
```

```
summary.tridim_transformation
```

Summary for a tridim_transformation object

Description

Summary for a tridim_transformation object

Usage

```
## S3 method for class 'tridim_transformation'
summary(object, ...)
```

Arguments

object	A tridim_transformation object
...	Unused

Value

Nothing, console output only.

Examples

```
euc2 <- fit_transformation(depV1+depV2~indepV1+indepV2,
  data = NakayaData,
  transformation = 'euclidean')
summary(euc2)
```

```
tridim_transformation-class
      Class tridim_transformation.
```

Description

Geometric transformations fitted with the [fit_transformation](#) function represented as a `tridim_transformation` object with information about transformation, data dimension, call formula, and fitted [stanfit](#) object,

Details

See `methods(class = "tridim_transformation")` for an overview of available methods.

Slots

`transformation` A string with the transformation name.

`formula` A [formula](#) object.

`Ndim` An integer with data dimension, either 2 or 3.

`data` A list containing variables used for the [sampling](#).

`stanmodel` A [stanmodel](#) used for sampling.

`stanfit` a [stanfit](#) object.

See Also

[fit_transformation](#)

```
waic.tridim_transformation
      Computes widely applicable information criterion (WAIC).
```

Description

Computes widely applicable information criterion via [loo](#) library. It can be used for a model comparison via [loo::loo_compare\(\)](#) function.

Usage

```
## S3 method for class 'tridim_transformation'
waic(x, ...)
```

Arguments

<code>x</code>	A <code>[tridim_transformation[tridim_transformation-class()]</code> object
<code>...</code>	unused

Value

A named list, see `loo::waic()` for details.

Examples

```
euc2 <- fit_transformation(depV1+depV2~indepV1+indepV2,  
  NakayaData, transformation = 'euclidean')  
aff2 <- fit_transformation(depV1+depV2~indepV1+indepV2,  
  NakayaData, transformation = 'affine')  
loo::loo_compare(waic(euc2), waic(aff2))
```

Index

* datasets

- CarbonExample1Data, [4](#)
- CarbonExample2Data, [5](#)
- CarbonExample3Data, [5](#)
- EyegazeData, [7](#)
- Face3D_M010, [7](#)
- Face3D_M101, [8](#)
- Face3D_M244, [8](#)
- Face3D_M92, [9](#)
- Face3D_W070, [9](#)
- Face3D_W097, [10](#)
- Face3D_W182, [10](#)
- Face3D_W243, [11](#)
- FriedmanKohlerData1, [14](#)
- FriedmanKohlerData2, [15](#)
- NakayaData, [16](#)
- _PACKAGE (TriDimRegression-package), [3](#)
- bayesplot::mcmc_intervals(), [17](#)
- CarbonExample1Data, [4](#)
- CarbonExample2Data, [5](#)
- CarbonExample3Data, [5](#)
- coef, [3](#)
- coef.tridim_transformation, [6](#)
- EyegazeData, [7](#)
- Face3D_M010, [7](#)
- Face3D_M101, [8](#)
- Face3D_M244, [8](#)
- Face3D_M92, [9](#)
- Face3D_W070, [9](#)
- Face3D_W097, [10](#)
- Face3D_W182, [10](#)
- Face3D_W243, [11](#)
- fit_transformation, [3](#), [11](#), [14](#), [18](#), [21](#)
- fit_transformation_df, [3](#), [11](#), [12](#), [13](#)
- formula, [21](#)
- FriedmanKohlerData1, [14](#)
- FriedmanKohlerData2, [15](#)
- is.tridim_transformation, [15](#)
- loo, [3](#), [21](#)
- loo.tridim_transformation, [16](#)
- loo::loo(), [16](#)
- loo::loo_compare(), [3](#), [21](#)
- loo::waic(), [22](#)
- NakayaData, [16](#)
- plot.tridim_transformation, [17](#)
- predict, [3](#)
- predict.tridim_transformation, [18](#)
- print.tridim_transformation, [19](#)
- R2, [3](#), [19](#)
- sampling, [12](#), [14](#), [21](#)
- stanfit, [21](#)
- stanmodel, [21](#)
- summary.tridim_transformation, [20](#)
- transformation_matrix, [3](#)
- tridim_transformation, [3](#), [6](#), [12](#), [14](#), [16–20](#)
- tridim_transformation
 - (tridim_transformation-class), [21](#)
- tridim_transformation-class, [21](#)
- TriDimRegression
 - (TriDimRegression-package), [3](#)
- TriDimRegression-package, [3](#)
- waic, [3](#)
- waic.tridim_transformation, [21](#)