

Package ‘batman’

July 22, 2025

Title Convert Categorical Representations of Logicals to Actual Logicals

Version 0.1.0

Date 2015-10-13

Author Oliver Keyes [aut, cre], Ruben C. Arslan [ctb], Christopher Akiki [ctb], Mine Cetinkaya-Rundel [ctb], Peter Meissner [ctb], Ilaria Prosdocimi [ctb], Thomas Leeper [ctb], Amy Lee [ctb], Adolfo Álvarez [ctb]

Maintainer Oliver Keyes <ironholds@gmail.com>

Description Survey systems and other third-party data sources commonly use non-standard representations of logical values when it comes to qualitative data - ``Yes'', ``No'' and ``N/A'', say. batman is a package designed to seamlessly convert these into logicals. It is highly localised, and contains equivalents to boolean values in languages including German, French, Spanish, Italian, Turkish, Chinese and Polish.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

URL <https://github.com/ironholds/batman>

BugReports <https://github.com/ironholds/batman/issues>

Suggests testthat

LinkingTo Rcpp

Imports Rcpp

NeedsCompilation yes

Repository CRAN

Date/Publication 2015-10-26 17:07:24

Contents

batman	2
categorical_booleans	2
get_languages	3
to_logical	3

Index	5
--------------	----------

batman	<i>Convert categorical representations of logicals to actual logicals</i>
--------	---

Description

Survey systems and other third-party data sources commonly use non-standard representations of logical values when it comes to qualitative data - "Yes", "No" and "N/A", say. batman is a package designed to seamlessly convert these into actual logical values.

See Also

`to_logical`

categorical_booleans	<i>TRUE/FALSE equivalents in categorical data for various languages</i>
----------------------	---

Description

A dataset containing the equivalents of TRUE or FALSE in categorical or user-submitted data, localised to various languages

Usage

`categorical_booleans`

Format

A list of named lists, each one containing two columns:

true a character vector of equivalents to TRUE

false a character vector of equivalents to FALSE

See Also

`to_logical`, which uses this dataset, and `get_languages` to see what languages are available.

get_languages	<i>Get language codes for batman-supported languages</i>
---------------	--

Description

retrieves a list of language codes for languages supported by the language parameter in `to_logical`.

Usage

```
get_languages()
```

See Also

`categorical_booleans`, the underlying dataset, or `to_logical`, which uses that dataset.

Examples

```
get_languages()
# [1] "en"
```

to_logical	<i>Convert categorical representations of true/false values to a logical</i>
------------	--

Description

`to_logical` is designed for the situation where you have categorical data (perhaps from a survey, or direct user input) that represents TRUE/FALSE values as something other than TRUE/FALSE - "Yes", "No", "None", "Y" or "False", say. With `to_logical` you can easily convert a vector of these values into an actual, logical vector, using either a predefined set of accepted TRUE or FALSE equivalents, or a set you specify yourself.

Usage

```
to_logical(x, language = "en", custom_true = character(),
  custom_false = character())
```

Arguments

x	a vector of categorical TRUE/FALSE/NA values.
language	the language to use. See <code>get_languages</code> for the list of supported languages. If your language is not supported, you can use <code>custom_true</code> and <code>custom_false</code> to provide values.
custom_true	a vector of values to consider, in addition to the ones <code>to_logical</code> already recognises, TRUE. Empty by default. Note that the comparison code is case-insensitive, so there's no need to include (for example) both "ja" and "Ja".
custom_false	a vector of values to consider, in addition to the ones <code>to_logical</code> already recognises, FALSE. Empty by default; see the notes on case sensitivity above.

Examples

```
# A very simple example using the pre-known true and false equivalents
categorical_values <- c("true","t","y","yes","f","no","1")
to_logical(categorical_values)

# Use a custom specifier
categorical_values <- c("NA","NA","NA","NA","NA","NA","NA","NA","Batman")
to_logical(categorical_values, custom_true = c("Batman"))
```

Index

* datasets

categorical_booleans, [2](#)

batman, [2](#)

batman-package (batman), [2](#)

categorical_booleans, [2](#), [3](#)

get_languages, [2](#), [3](#)

to_logical, [2](#), [3](#), [3](#)