

Package ‘geomaroc’

July 22, 2025

Title Easily Visualize Geographic Data of Morocco

Version 0.1.1

Maintainer Amine Andam <andamamine83@gmail.com>

Description Tools to easily visualize geographic data of Morocco.

This package interacts with data available through the 'geomarocdata' package, which is available in a 'drat' repository. The size of the 'geomarocdata' package is approximately 12 MB.

License GPL

Imports jsonlite , sf

Encoding UTF-8

URL <https://github.com/AmineAndam04/R-geomaroc>

RoxygenNote 7.1.0

Suggests knitr, rmarkdown, testthat, geomarocdata

Additional_repositories <https://amineandam04.github.io/drat/>

VignetteBuilder knitr

NeedsCompilation no

Author Amine Andam [aut, cre]

Repository CRAN

Date/Publication 2022-05-13 16:00:06 UTC

Contents

getDistrict	2
getMultiDistrict	2
getMultiProvince	3
getMultiRegion	4
getPathRegion	5
getProvince	5
getRegion	6
provinces	6
regions	7

Index**8**

getDistrict	<i>Plot districts within a province</i>
-------------	---

Description

Helps to plot the shape of districts within a province.

Usage

```
getDistrict(n_province = NULL, id = NULL)
```

Arguments

n_province	The name of the province to plot. The notation should be respected.To get the notation: provinces()
id	the id of the province.To get the id of each province provinces()

Value

return a sf object

Examples

```
## Not run:  
#Use DISTRICT name  
prov=getDistrict("Casablanca")  
plot(prov$coordinates)  
#Use id  
prov=getDistrict(id=141)  
plot(prov$coordinates)  
  
## End(Not run)
```

getMultiDistrict	<i>Plot districts of multiple provinces</i>
------------------	---

Description

Helps to plot the shape of districts of multiple provinces.

Usage

```
getMultiDistrict(n_province = NULL, id = NULL)
```

Arguments

n_province	vector of The name of the province to plot. The notation should be respected.To get the notation: provinces()
id	vector of provinces id.Each province has an id. To get the id of each province : provinces()

Value

return a sf object

Examples

```
## Not run:
prov=getMultiDistrict(c("Tanger-Assilah", "Fahs-Anjra"))
plot(prov$coordinates)
prov=getMultiDistrict(id=c(227,511))
plot(prov$coordinates)

## End(Not run)
```

getMultiProvince	<i>Plot multiple regions</i>
------------------	------------------------------

Description

Helps to plot the shape of multiple regions.

Usage

```
getMultiProvince(n_region = NULL, id = NULL)
```

Arguments

n_region	vector of the name of the regions to plot. The notation should be respected.To get the notation execute: regions()
id	vector of regions id.Each region has an id. To get the id of each region please execute : regions()

Value

return a sf object

Examples

```
## Not run:
# Plot two regions :Casablanca-Settat and Rabat-Sale-Kenitra
regions=getMultiProvince(c("Casablanca-Settat","Rabat-Sale-Kenitra"))
plot(regions$coordinates)
#Plot provinces of Oriental and Tanger-Tetouan-AL-Hoceima
regions=getMultiProvince(id=c(1,2))
plot(regions$coordinates)

## End(Not run)
```

getMultiRegion	<i>Plot multiple regions</i>
----------------	------------------------------

Description

Helps to plot the shape of multiple regions.

Usage

```
getMultiRegion(name = NULL, id = NULL)
```

Arguments

name	vector of the name of the regions to plot. The notation should be respected.To get the notation execute: regions()
id	vector of regions id.Each region has an id. To get the id of each region please execute : regions()

Value

return a sf object

Examples

```
## Not run:
#Plot two regions :Casablanca-Settat and Laayoune-Sakia-El-Hamra
regions=getMultiRegion(c("Eddakhla-Oued-Eddahab","Laayoune-Sakia-El-Hamra"))
plot(regions$coordinates)
#Plot the map of Morocco
mar=getMultiRegion(id=1:12)
plot(mar$coordinates)

## End(Not run)
```

getPathRegion	<i>Internal function</i>
---------------	--------------------------

Description

Internal function

Usage

```
getPathRegion(n_region = NULL, id = NULL)
```

Arguments

n_region	name
id	id of region

getProvince	<i>Plot provinces within a region</i>
-------------	---------------------------------------

Description

Helps to plot the shape of provinces within a region.

Usage

```
getProvince(n_region = NULL, id = NULL)
```

Arguments

n_region	The name of the region to plot. The notation should be respected. To get the notation : regions()
id	Each region has an id. To get the id of each region : regions()

Value

return a sf object

Examples

```
## Not run:
#Use region name
region=getProvince("Tanger-Tetouan-Al-Hoceima")
plot(region$coordinates)
#Use id
region=getProvince(id=1) #Don't forget getRegion(id=1) not getRegion(1)
plot(region$coordinates)

## End(Not run)
```

getRegion	<i>Plot regions</i>
-----------	---------------------

Description

plot the shape of each region

Usage

```
getRegion(name = NULL, id = NULL)
```

Arguments

name	The name of the region to plot. The notation should be respected. To get the notation execute: regions()
id	Each region has an id. To get the id of each region please execute : regions()

Value

return a sf object

Examples

```
## Not run:

region=getRegion("Tanger-Tetouan-Al-Hoceima") #Use region name
#plot(region$coordinates)
region=getRegion(id=1) # use id
plot(region$coordinates)

## End(Not run)
```

provinces	<i>Notation : provinces</i>
-----------	-----------------------------

Description

Hepls to respect the notation and to get the id and the name of each province

Usage

```
provinces()
```

Value

return a dataframe

Examples

```
## Not run:  
province=provinces()  
province  
  
## End(Not run)
```

regions

Notation : regions

Description

Hepls to respect the notation and to get the id and the name of each region

Usage

```
regions()
```

Value

return a dataframe

Examples

```
## Not run:  
region=regions()  
region  
## End(Not run)
```

Index

`getDistrict`, [2](#)
`getMultiDistrict`, [2](#)
`getMultiProvince`, [3](#)
`getMultiRegion`, [4](#)
`getPathRegion`, [5](#)
`getProvince`, [5](#)
`getRegion`, [6](#)

`provinces`, [6](#)

`regions`, [7](#)