

Package ‘prettyB’

July 23, 2025

Type Package

Title Pretty Base Graphics

Version 0.2.2

Maintainer Colin Gillespie <csgillespie@gmail.com>

Description Drop-in replacements for standard base graphics functions. The replacements are prettier versions of the originals.

License GPL-2 | GPL-3

URL <https://github.com/jumpingrivers/prettyB/>

BugReports <https://github.com/jumpingrivers/prettyB/issues>

Imports graphics, grDevices, stats

Suggests covr, knitr, lintr, rmarkdown, testthat, vdiff

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

NeedsCompilation no

Author Colin Gillespie [aut, cre]

Repository CRAN

Date/Publication 2021-02-10 13:50:03 UTC

Contents

prettyB-package	2
add_x_axis	2
barplot.prettyB	3
boxplot.prettyB	5
hist.prettyB	6
plot.prettyB	8
reset_prettyB	9

Index	10
--------------	-----------

prettyB-package

The prettyB package

Description

Anyone who uses R Base graphics, have a 100 and 1 tweaks that they use to make the figures more presentable. This package aims to capture the tweaks in one place. By masking_standard plotting functions, we can automatically make base graphics a bit more pretty.

Author(s)

<csgillespie@gmail.com>

See Also

<https://github.com/jumpingrivers/prettyB>

add_x_axis

Add tick marks to x/y axis A nicer set of default tick marks

Description

Add tick marks to x/y axis

A nicer set of default tick marks

Usage

```
add_x_axis(ticks_x, labels = ticks_x, tick = TRUE, lwd = 0, lwd.ticks = 1)
```

```
add_y_axis(ticks_y, labels = ticks_y, tick = TRUE, lwd = 0, lwd.ticks = 1)
```

Arguments

ticks_x	location of x tick mark
labels	tick label
tick	Display tick mark
lwd	width of line
lwd.ticks	width of tick mark
ticks_y	location of y tick mark

barplot.prettyB	<i>PrettyB barplot.default function</i>
-----------------	---

Description

This function overrides the default arguments. See `?graphics::barplot.default`

Usage

```
## S3 method for class 'prettyB'
barplot(
  height,
  width = 1,
  space = NULL,
  names.arg = NULL,
  legend.text = NULL,
  beside = FALSE,
  horiz = FALSE,
  density = NULL,
  angle = 45,
  col = NULL,
  border = par("fg"),
  main = NULL,
  sub = NULL,
  xlab = NULL,
  ylab = NULL,
  xlim = NULL,
  ylim = NULL,
  xpd = TRUE,
  log = "",
  axes = TRUE,
  axisnames = TRUE,
  cex.axis = par("cex.axis"),
  cex.names = par("cex.axis"),
  inside = TRUE,
  plot = TRUE,
  axis.lty = 0,
  offset = 0,
  add = FALSE,
  args.legend = NULL,
  ...
)

barplot_p(
  height,
  width = 1,
  space = NULL,
```


Examples

```
barplot(VADeaths)
```

```
boxplot.prettyB
```

```
PrettyB boxplot.default function
```

Description

This function overrides the default arguments. See `?graphics::boxplot.default`

Usage

```
## S3 method for class 'prettyB'
boxplot(
  x,
  ...,
  range = 1.5,
  width = NULL,
  varwidth = FALSE,
  notch = FALSE,
  outline = TRUE,
  names,
  plot = TRUE,
  border = par("fg"),
  col = NULL,
  log = "",
  pars = list(boxwex = 0.8, staplewex = 0.5, outwex = 0.5),
  horizontal = FALSE,
  add = FALSE,
  at = NULL
)

boxplot_p(
  x,
  ...,
  range = 1.5,
  width = NULL,
  varwidth = FALSE,
  notch = FALSE,
  outline = TRUE,
  names,
  plot = TRUE,
  border = par("fg"),
  col = NULL,
  log = "",
  pars = list(boxwex = 0.8, staplewex = 0.5, outwex = 0.5),
```

```

    horizontal = FALSE,
    add = FALSE,
    at = NULL
  )

```

Arguments

```

x, ..., range, width
    See ?graphics::boxplot.default
varwidth, notch, outline
    See ?graphics::boxplot.default
names, plot, border
    See ?graphics::boxplot.default
col, log, pars
    See ?graphics::boxplot.default
horizontal, add, at
    See ?graphics::boxplot.default

```

hist.prettyB

PrettyB hist.default function

Description

This function overrides the default arguments. See `?graphics::hist.default`

Usage

```

## S3 method for class 'prettyB'
hist(
  x,
  breaks = "Sturges",
  freq = NULL,
  probability = !freq,
  include.lowest = TRUE,
  right = TRUE,
  density = NULL,
  angle = 45,
  col = NULL,
  border = NULL,
  main = paste("Histogram of", xname),
  xlim = range(breaks),
  ylim = NULL,
  xlab = xname,
  ylab,
  axes = TRUE,
  plot = TRUE,
  labels = FALSE,

```

```
    nclass = NULL,  
    warn.unused = TRUE,  
    ...  
)  
  
hist_p(  
  x,  
  breaks = "Sturges",  
  freq = NULL,  
  probability = !freq,  
  include.lowest = TRUE,  
  right = TRUE,  
  density = NULL,  
  angle = 45,  
  col = NULL,  
  border = NULL,  
  main = paste("Histogram of", xname),  
  xlim = range(breaks),  
  ylim = NULL,  
  xlab = xname,  
  ylab,  
  axes = TRUE,  
  plot = TRUE,  
  labels = FALSE,  
  nclass = NULL,  
  warn.unused = TRUE,  
  ...  
)
```

Arguments

x, breaks, freq, probability	See ?graphics::hist.default
include.lowest, right, density	
	See ?graphics::hist.default
angle, col, border, main	
	See ?graphics::hist.default
xlim, ylim, xlab, ylab, axes, plot	
	See ?graphics::hist.default
labels, nclass, warn.unused	
	See ?graphics::hist.default
...	See ?graphics::hist.default

Examples

```
x = rlnorm(100)  
hist(x)
```

plot.prettyB	<i>PrettyB plot.default function</i>
--------------	--------------------------------------

Description

This function overrides the default arguments. See `?graphics::plot.default`

Usage

```
## S3 method for class 'prettyB'
plot(
  x,
  y = NULL,
  type = "p",
  xlim = NULL,
  ylim = NULL,
  log = "",
  main = NULL,
  sub = NULL,
  xlab = NULL,
  ylab = NULL,
  ann = par("ann"),
  axes = TRUE,
  frame.plot = axes,
  panel.first = NULL,
  panel.last = NULL,
  asp = NA,
  ...
)

plot_p(
  x,
  y = NULL,
  type = "p",
  xlim = NULL,
  ylim = NULL,
  log = "",
  main = NULL,
  sub = NULL,
  xlab = NULL,
  ylab = NULL,
  ann = par("ann"),
  axes = TRUE,
  frame.plot = axes,
  panel.first = NULL,
  panel.last = NULL,
  asp = NA,
```

```
    ...
  )
```

Arguments

x, y, type, log	See ?graphics::plot.default
xlim, ylim	See ?graphics::plot.default
main, sub, xlab, ylab	See ?graphics::plot.default
ann, axes	See ?graphics::plot.default
frame.plot, panel.first, panel.last	See ?graphics::plot.default
asp	See ?graphics::plot.default
...	See ?graphics::plot.default

Examples

```
plot_p(1:10, 1:10)
```

reset_prettyB	<i>Set up par and palette</i>	<i>Sets up par and palette</i>
---------------	-------------------------------	--------------------------------

Description

Set up par and palette
 Sets up par and palette

Usage

```
reset_prettyB()

setup_prettyB()
```

Index

*** package**

prettyB-package, [2](#)

add_x_axis, [2](#)

add_y_axis (add_x_axis), [2](#)

barplot.prettyB, [3](#)

barplot_p (barplot.prettyB), [3](#)

boxplot.prettyB, [5](#)

boxplot_p (boxplot.prettyB), [5](#)

hist.prettyB, [6](#)

hist_p (hist.prettyB), [6](#)

plot.prettyB, [8](#)

plot_p (plot.prettyB), [8](#)

prettyB (prettyB-package), [2](#)

prettyb (prettyB-package), [2](#)

prettyB-package, [2](#)

reset_prettyB, [9](#)

setup_prettyB (reset_prettyB), [9](#)