

Package ‘qPCRtools’

July 22, 2025

Version 1.0.1

Title Tools for qPCR

Description PKG_DESC.

URL <https://github.com/lixiang117423/qPCRtools>

BugReports <https://github.com/lixiang117423/qPCRtools/issues>

License MIT + file LICENSE

Imports broom, dplyr, ggplot2, ggpmisc, ggthemes, kableExtra,
magrittr, multcomp, rstatix, stats, tibble, tidyr

RoxygenNote 7.2.3

NeedsCompilation no

Author Xiang LI [cre, aut]

Maintainer Xiang LI <lixiang117423@gmail.com>

Repository CRAN

Date/Publication 2023-11-02 13:10:05 UTC

Contents

CalCurve	2
CalExp2dCt	3
CalExp2ddCt	3
CalExpCurve	5
CalExpRqPCR	6
CalRTable	7
Index	8

CalCurve

*Standard Curve Calculation.***Description**

The function can calculate the standard curve. At the same time, it can get the amplification efficiency of primer(s). Based on the amplification efficiency, we can know which method can be used to calculate the expression level.

Arguments

cq.table	The data frame of the position and Cq value.
concen.table	The data frame of the position and concentration.
highest.concen	The highest concentration for calculation.
lowest.concen	The lowest concentration for calculation.
dilution	Dilution factor of cDNA template. The default value is 4.
by.mean	Calculation by mean Cq value or not. The default value is TRUE.

Value

A list.

Author(s)

Xiang LI <lixiang117423@gmail.com>

Examples

```
df.1.path <- system.file("examples", "calsc.cq.txt", package = "qPCRtools")
df.2.path <- system.file("examples", "calsc.info.txt", package = "qPCRtools")
df.1 <- read.table(df.1.path, header = TRUE)
df.2 <- read.table(df.2.path, header = TRUE)
CalCurve(
  cq.table = df.1,
  concen.table = df.2,
  lowest.concen = 4,
  highest.concen = 4096,
  dilu = 4,
  by = "mean"
) -> p

p[["table"]]
p[["figure"]]
```

CalExp2dCt*Calculate expression using standard curve.*

Description

Calculate expression using standard curve.

Arguments

cq.table The data frame of the position and cq value.
design.table The data frame of the position and corresponding information.
ref.gene The name of reference gene.

Value

A list contain a table and a figure.

Author(s)

Xiang LI <lixiang117423@gmail.com>

Examples

```
df1.path <- system.file("examples", "dct.cq.txt", package = "qPCRtools")
df2.path <- system.file("examples", "dct.design.txt", package = "qPCRtools")
cq.table <- read.table(df1.path, sep = ",", header = TRUE)
design.table <- read.table(df2.path, sep = ",", header = TRUE)
CalExp2dCt(cq.table,
            design.table,
            ref.gene = "Actin"
) -> res
```

CalExp2ddCt*Calculate expression using standard curve.*

Description

Calculate expression using standard curve.

Arguments

cq.table	The data frame of the position and cq value.
design.table	The data frame of the position and corresponding information.
correction	Correct expression value by reference gene.
ref.gene	The name of reference gene.
ref.group	The name of reference group.
stat.method	Statistical method.
remove.outliers	Remove the outliers of each group and gene, or not.
fig.type	Output image type, 'box' represents 'boxplot', 'bar' represents 'barplot'.
fig.ncol	Number of colums of figure.

Value

A list contain a table and a figure.

Author(s)

Xiang LI <lixiang117423@gmail.com>

Examples

```
df1.path = system.file("examples", "ddct.cq.txt", package = "qPCRtools")
df2.path = system.file("examples", "ddct.design.txt", package = "qPCRtools")

cq.table = read.table(df1.path, header = TRUE)
design.table = read.table(df2.path, header = TRUE)

CalExp2ddCt(cq.table,
            design.table,
            ref.gene = "OsUBQ",
            ref.group = "CK",
            stat.method = "t.test",
            remove.outliers = TRUE,
            fig.type = "box",
            fig.ncol = NULL) -> res

res[["table"]]
res[["figure"]]
```

CalExpCurve	<i>Calculate expression using standard curve.</i>
-------------	---

Description

Calculate expression using standard curve.

Arguments

cq.table	The data frame of the position and Cq value.
design.table	The data frame of the position and corresponding information.
correction	Correct expression value by reference gene.
ref.gene	The name of reference gene.
stat.method	Statistical method.
ref.group	The name of reference group.
fig.type	Output image type, 'box' represents 'boxplot', 'bar' represents 'barplot'.
fig.ncol	Number of columen of figure.

Value

A list contain a table and a figure.

Author(s)

Xiang LI <lixiang117423@gmail.com>

Examples

```
df1.path = system.file("examples", "cal.exp.curve.cq.txt", package = "qPCRtools")
df2.path = system.file("examples", "cal.expre.curve.sdc.txt", package = "qPCRtools")
df3.path = system.file("examples", "cal.exp.curve.design.txt", package = "qPCRtools")

cq.table = read.table(df1.path, header = TRUE)
curve.table = read.table(df2.path, sep = "\t", header = TRUE)
design.table = read.table(df3.path, header = TRUE)

CalExpCurve(
  cq.table,
  curve.table,
  design.table,
  correction = TRUE,
  ref.gene = "OsUBQ",
  stat.method = "t.test",
  ref.group = "CK",
  fig.type = "box",
  fig.ncol = NULL) -> res
```

```
res[["table"]]
res[["figure"]]
```

CalExpRqPCR

Calculate expression using standard curve.

Description

Calculate expression using standard curve.

Arguments

cq.table	The data frame of the position and cq value.
design.table	The data frame of the position and corresponding information.
correction	Correct expression value by reference gene.
ref.gene	The name of reference gene.
ref.group	The name of reference group.
stat.method	Statistical method.
fig.type	Output image type, 'box' represents 'boxplot', 'bar' represents 'barplot'.
fig.ncol	Number of columes of figure.

Value

A list contain a table and a figure.

Author(s)

Xiang LI <lixiang117423@gmail.com>

Examples

```
df1.path <- system.file("examples", "cal.expre.rqpcr.cq.txt", package = "qPCRtools")
df2.path <- system.file("examples", "cal.expre.rqpcr.design.txt", package = "qPCRtools")

cq.table <- read.table(df1.path, header = TRUE)
design.table <- read.table(df2.path, header = TRUE)

CalExpRqPCR(cq.table,
             design.table,
             ref.gene = NULL,
             ref.group = "CK",
             stat.method = "t.test",
             fig.type = "box",
             fig.ncol = NULL
             ) -> res
```

```
res[["table"]]
res[["figure"]]
```

CalRTable*Calculate RNA volume for reverse transcription.*

Description

The first step of qPCR is usually the preparation of cDNA. We need to calculate the column of RNA for reverse transcription to cDNA. So, if we have the concentration of RNA, we can use the function 'CalRTable' to do that.

Arguments

data	A data.frame contained the sample names and the concentration value. The default unit of concentration is ng/uL.
template	A data.frame contained the information of reverse transcription. In this data.frame there must be a column called 'all'.
RNA.weight	RNA weight required for reverse transcription. Default is 1 ug.

Value

A list contain a table and a figure.

Author(s)

Xiang LI <lixiang117423@gmail.com>

Examples

```
df.1.path <- system.file("examples", "crtv.data.txt", package = "qPCRtools")
df.2.path <- system.file("examples", "crtv.template.txt", package = "qPCRtools")
df.1 <- read.table(df.1.path, sep = "\t", header = TRUE)
df.2 <- read.table(df.2.path, sep = "\t", header = TRUE)
result <- CalRTable(data = df.1, template = df.2, RNA.weight = 2)
head(result)
```

Index

CalCurve, [2](#)
CalExp2dCt, [3](#)
CalExp2ddCt, [3](#)
CalExpCurve, [5](#)
CalExpRqPCR, [6](#)
CalRTable, [7](#)