

Package ‘reshape2’

July 23, 2025

Title Flexibly Reshape Data: A Reboot of the Reshape Package

Version 1.4.4

Author Hadley Wickham <h.wickham@gmail.com>

Maintainer Hadley Wickham <h.wickham@gmail.com>

Description Flexibly restructure and aggregate data using just two functions: melt and 'dcast' (or 'acast').

License MIT + file LICENSE

URL <https://github.com/hadley/reshape>

BugReports <https://github.com/hadley/reshape/issues>

Depends R (>= 3.1)

Imports plyr (>= 1.8.1), Rcpp, stringr

Suggests covr, lattice, testthat (>= 0.8.0)

LinkingTo Rcpp

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

NeedsCompilation yes

Repository CRAN

Date/Publication 2020-04-09 13:50:02 UTC

Contents

add_margins	2
cast	2
colsplit	5
french_fries	5
melt	6
melt.array	7
melt.data.frame	8

melt.default	9
melt.list	10
melt_check	11
parse_formula	11
recast	12
smiths	13
tips	13

Index	14
--------------	-----------

add_margins	<i>Add margins to a data frame.</i>
-------------	-------------------------------------

Description

Rownames are silently stripped. All margining variables will be converted to factors.

Usage

```
add_margins(df, vars, margins = TRUE)
```

Arguments

df	input data frame
vars	a list of character vectors giving the variables in each dimension
margins	a character vector of variable names to compute margins for. TRUE will compute all possible margins.

cast	<i>Cast functions Cast a molten data frame into an array or data frame.</i>
------	---

Description

Use acast or dcast depending on whether you want vector/matrix/array output or data frame output. Data frames can have at most two dimensions.

Usage

```
dcast(  
  data,  
  formula,  
  fun.aggregate = NULL,  
  ...,  
  margins = NULL,  
  subset = NULL,  
  fill = NULL,
```

```

    drop = TRUE,
    value.var = guess_value(data)
  )

  acast(
    data,
    formula,
    fun.aggregate = NULL,
    ...,
    margins = NULL,
    subset = NULL,
    fill = NULL,
    drop = TRUE,
    value.var = guess_value(data)
  )

```

Arguments

<code>data</code>	molten data frame, see melt .
<code>formula</code>	casting formula, see details for specifics.
<code>fun.aggregate</code>	aggregation function needed if variables do not identify a single observation for each output cell. Defaults to length (with a message) if needed but not specified.
<code>...</code>	further arguments are passed to aggregating function
<code>margins</code>	vector of variable names (can include "grand\col" and "grand\row") to compute margins for, or TRUE to compute all margins . Any variables that can not be margined over will be silently dropped.
<code>subset</code>	quoted expression used to subset data prior to reshaping, e.g. <code>subset = .(variable=="length")</code> .
<code>fill</code>	value with which to fill in structural missings, defaults to value from applying <code>fun.aggregate</code> to 0 length vector
<code>drop</code>	should missing combinations dropped or kept?
<code>value.var</code>	name of column which stores values, see guess_value for default strategies to figure this out.

Details

The cast formula has the following format: `x_variable + x_2 ~ y_variable + y_2 ~ z_variable ~ ...`. The order of the variables makes a difference. The first varies slowest, and the last fastest. There are a couple of special variables: `"..."` represents all other variables not used in the formula and `"."` represents no variable, so you can do `formula = var1 ~ ..`

Alternatively, you can supply a list of quoted expressions, in the form `list(.(x_variable, x_2), .(y_variable, y_2), .(z))`. The advantage of this form is that you can cast based on transformations of the variables: `list(.(a + b), (c = round(c)))`. See the documentation for `.` for more details and alternative formats.

If the combination of variables you supply does not uniquely identify one row in the original data set, you will need to supply an aggregating function, `fun.aggregate`. This function should take a vector of numbers and return a single summary statistic.

See Also

`melt`, <http://had.co.nz/reshape/>

Examples

```
#Air quality example
names(airquality) <- tolower(names(airquality))
aqm <- melt(airquality, id=c("month", "day"), na.rm=TRUE)

acast(aqm, day ~ month ~ variable)
acast(aqm, month ~ variable, mean)
acast(aqm, month ~ variable, mean, margins = TRUE)
dcast(aqm, month ~ variable, mean, margins = c("month", "variable"))

library(plyr) # needed to access . function
acast(aqm, variable ~ month, mean, subset = .(variable == "ozone"))
acast(aqm, variable ~ month, mean, subset = .(month == 5))

#Chick weight example
names(ChickWeight) <- tolower(names(ChickWeight))
chick_m <- melt(ChickWeight, id=2:4, na.rm=TRUE)

dcast(chick_m, time ~ variable, mean) # average effect of time
dcast(chick_m, diet ~ variable, mean) # average effect of diet
acast(chick_m, diet ~ time, mean) # average effect of diet & time

# How many chicks at each time? - checking for balance
acast(chick_m, time ~ diet, length)
acast(chick_m, chick ~ time, mean)
acast(chick_m, chick ~ time, mean, subset = .(time < 10 & chick < 20))

acast(chick_m, time ~ diet, length)

dcast(chick_m, diet + chick ~ time)
acast(chick_m, diet + chick ~ time)
acast(chick_m, chick ~ time ~ diet)
acast(chick_m, diet + chick ~ time, length, margins="diet")
acast(chick_m, diet + chick ~ time, length, drop = FALSE)

#Tips example
dcast(melt(tips), sex ~ smoker, mean, subset = .(variable == "total_bill"))

ff_d <- melt(french_fries, id=1:4, na.rm=TRUE)
acast(ff_d, subject ~ time, length)
acast(ff_d, subject ~ time, length, fill=0)
dcast(ff_d, treatment ~ variable, mean, margins = TRUE)
dcast(ff_d, treatment + subject ~ variable, mean, margins="treatment")
if (require("lattice")) {
  lattice::xyplot(`1` ~ `2` | variable, dcast(ff_d, ... ~ rep), aspect="iso")
}
```

`colsplit`*Split a vector into multiple columns*

Description

Useful for splitting variable names that a combination of multiple variables. Uses `type.convert` to convert each column to correct type, but will not convert character to factor.

Usage

```
colsplit(string, pattern, names)
```

Arguments

<code>string</code>	character vector or factor to split up
<code>pattern</code>	regular expression to split on
<code>names</code>	names for output columns

Examples

```
x <- c("a_1", "a_2", "b_2", "c_3")
vars <- colsplit(x, "_", c("trt", "time"))
vars
str(vars)
```

`french_fries`*Sensory data from a french fries experiment.*

Description

This data was collected from a sensory experiment conducted at Iowa State University in 2004. The investigators were interested in the effect of using three different fryer oils had on the taste of the fries.

Usage

```
french_fries
```

Format

A data frame with 696 rows and 9 variables

Details

Variables:

- time in weeks from start of study.
- treatment (type of oil),
- subject,
- replicate,
- potato-y flavour,
- buttery flavour,
- grassy flavour,
- rancid flavour,
- painty flavour

melt

Convert an object into a molten data frame.

Description

This the generic melt function. See the following functions for the details about different data structures:

Usage

```
melt(data, ..., na.rm = FALSE, value.name = "value")
```

Arguments

data	Data set to melt
...	further arguments passed to or from other methods.
na.rm	Should NA values be removed from the data set? This will convert explicit missings to implicit missings.
value.name	name of variable used to store values

Details

- [melt.data.frame](#) for data.frames
- [melt.array](#) for arrays, matrices and tables
- [melt.list](#) for lists

See Also

[cast](#)

melt.array	<i>Melt an array.</i>
------------	-----------------------

Description

This code is conceptually similar to [as.data.frame.table](#)

Usage

```
## S3 method for class 'array'
melt(
  data,
  varnames = names(dimnames(data)),
  ...,
  na.rm = FALSE,
  as.is = FALSE,
  value.name = "value"
)

## S3 method for class 'table'
melt(
  data,
  varnames = names(dimnames(data)),
  ...,
  na.rm = FALSE,
  as.is = FALSE,
  value.name = "value"
)

## S3 method for class 'matrix'
melt(
  data,
  varnames = names(dimnames(data)),
  ...,
  na.rm = FALSE,
  as.is = FALSE,
  value.name = "value"
)
```

Arguments

data	array to melt
varnames	variable names to use in molten data.frame
...	further arguments passed to or from other methods.
na.rm	Should NA values be removed from the data set? This will convert explicit missings to implicit missings.

as.is	if FALSE, the default, dimnames will be converted using <code>type.convert</code> . If TRUE, they will be left as strings.
value.name	name of variable used to store values

See Also`cast`Other melt methods: `melt.data.frame()`, `melt.default()`, `melt.list()`**Examples**

```
a <- array(c(1:23, NA), c(2,3,4))
melt(a)
melt(a, na.rm = TRUE)
melt(a, varnames=c("X","Y","Z"))
dimnames(a) <- lapply(dim(a), function(x) LETTERS[1:x])
melt(a)
melt(a, varnames=c("X","Y","Z"))
dimnames(a)[1] <- list(NULL)
melt(a)
```

melt.data.frame	<i>Melt a data frame into form suitable for easy casting.</i>
-----------------	---

Description

You need to tell melt which of your variables are id variables, and which are measured variables. If you only supply one of `id.vars` and `measure.vars`, melt will assume the remainder of the variables in the data set belong to the other. If you supply neither, melt will assume factor and character variables are id variables, and all others are measured.

Usage

```
## S3 method for class 'data.frame'
melt(
  data,
  id.vars,
  measure.vars,
  variable.name = "variable",
  ...,
  na.rm = FALSE,
  value.name = "value",
  factorsAsStrings = TRUE
)
```

Arguments

data	data frame to melt
id.vars	vector of id variables. Can be integer (variable position) or string (variable name). If blank, will use all non-measured variables.
measure.vars	vector of measured variables. Can be integer (variable position) or string (variable name). If blank, will use all non id.vars
variable.name	name of variable used to store measured variable names
...	further arguments passed to or from other methods.
na.rm	Should NA values be removed from the data set? This will convert explicit missings to implicit missings.
value.name	name of variable used to store values
factorsAsStrings	Control whether factors are converted to character when melted as measure variables. When FALSE, coercion is forced if levels are not identical across the measure.vars.

See Also[cast](#)Other melt methods: [melt.array\(\)](#), [melt.default\(\)](#), [melt.list\(\)](#)**Examples**

```
names(airquality) <- tolower(names(airquality))
melt(airquality, id=c("month", "day"))
names(ChickWeight) <- tolower(names(ChickWeight))
melt(ChickWeight, id=2:4)
```

melt.default	<i>Melt a vector. For vectors, makes a column of a data frame</i>
--------------	---

Description

Melt a vector. For vectors, makes a column of a data frame

Usage

```
## Default S3 method:
melt(data, ..., na.rm = FALSE, value.name = "value")
```

Arguments

data	vector to melt
...	further arguments passed to or from other methods.
na.rm	Should NA values be removed from the data set? This will convert explicit missings to implicit missings.
value.name	name of variable used to store values

See Also[melt](#), [cast](#)Other melt methods: [melt.array\(\)](#), [melt.data.frame\(\)](#), [melt.list\(\)](#)

melt.list*Melt a list by recursively melting each component.*

Description

Melt a list by recursively melting each component.

Usage

```
## S3 method for class 'list'
melt(data, ..., level = 1)
```

Arguments

data	list to recursively melt
...	further arguments passed to or from other methods.
level	list level - used for creating labels

See Also[cast](#)Other melt methods: [melt.array\(\)](#), [melt.data.frame\(\)](#), [melt.default\(\)](#)**Examples**

```
a <- as.list(c(1:4, NA))
melt(a)
names(a) <- letters[1:4]
melt(a)
a <- list(matrix(1:4, ncol=2), matrix(1:6, ncol=2))
melt(a)
a <- list(matrix(1:4, ncol=2), array(1:27, c(3,3,3)))
melt(a)
melt(list(1:5, matrix(1:4, ncol=2)))
melt(list(list(1:3), 1, list(as.list(3:4), as.list(1:2))))
```

melt_check	<i>Check that input variables to melt are appropriate.</i>
------------	--

Description

If `id.vars` or `measure.vars` are missing, `melt_check` will do its best to impute them. If you only supply one of `id.vars` and `measure.vars`, melt will assume the remainder of the variables in the data set belong to the other. If you supply neither, melt will assume discrete variables are id variables and all other are measured.

Usage

```
melt_check(data, id.vars, measure.vars, variable.name, value.name)
```

Arguments

<code>data</code>	data frame
<code>id.vars</code>	vector of identifying variable names or indexes
<code>measure.vars</code>	vector of Measured variable names or indexes
<code>variable.name</code>	name of variable used to store measured variable names
<code>value.name</code>	name of variable used to store values

Value

a list giving id and measure variables names.

<code>parse_formula</code>	<i>Parse casting formulae.</i>
----------------------------	--------------------------------

Description

There are a two ways to specify a casting formula: either as a string, or a list of quoted variables. This function converts the former to the latter.

Usage

```
parse_formula(formula = "... ~ variable", varnames, value.var = "value")
```

Arguments

<code>formula</code>	formula to parse
<code>varnames</code>	names of all variables in data
<code>value.var</code>	name of variable containing values

Details

Casting formulas separate dimensions with ~ and variables within a dimension with + or *. . can be used as a placeholder, and ... represents all other variables not otherwise used.

Examples

```
reshape2::parse_formula("a + ...", letters[1:6])
reshape2::parse_formula("a ~ b + d")
reshape2::parse_formula("a + b ~ c ~ .")
```

recast

Recast: melt and cast in a single step

Description

This conveniently wraps melting and (d)casting a data frame into a single step.

Usage

```
recast(data, formula, ..., id.var, measure.var)
```

Arguments

data	data set to melt
formula	casting formula, see dcast for specifics
...	other arguments passed to dcast
id.var	identifying variables. If blank, will use all non measure.var variables
measure.var	measured variables. If blank, will use all non id.var variables

See Also

<http://had.co.nz/reshape/>

Examples

```
recast(french_fries, time ~ variable, id.var = 1:4)
```

smiths*Demo data describing the Smiths.*

Description

A small demo dataset describing John and Mary Smith. Used in the introductory vignette.

Usage

smiths

Format

A data frame with 2 rows and 5 variables

tips*Tipping data*

Description

One waiter recorded information about each tip he received over a period of a few months working in one restaurant. He collected several variables:

Usage

tips

Format

A data frame with 244 rows and 7 variables

Details

- tip in dollars,
- bill in dollars,
- sex of the bill payer,
- whether there were smokers in the party,
- day of the week,
- time of day,
- size of the party.

In all he recorded 244 tips. The data was reported in a collection of case studies for business statistics (Bryant & Smith 1995).

References

Bryant, P. G. and Smith, M (1995) *Practical Data Analysis: Case Studies in Business Statistics*. Homewood, IL: Richard D. Irwin Publishing:

Index

- * **datasets**
 - french_fries, [5](#)
 - smiths, [13](#)
 - tips, [13](#)
- * **manip**
 - cast, [2](#)
 - colsplit, [5](#)
 - melt, [6](#)
 - melt.array, [7](#)
 - melt.data.frame, [8](#)
 - melt.default, [9](#)
 - melt.list, [10](#)
 - recast, [12](#)
- * **melt methods**
 - melt.array, [7](#)
 - melt.data.frame, [8](#)
 - melt.default, [9](#)
 - melt.list, [10](#)
- ., [3](#)
- acast (cast), [2](#)
- add_margins, [2](#)
- as.data.frame.table, [7](#)
- cast, [2](#), [6](#), [8–10](#)
- colsplit, [5](#)
- dcast, [12](#)
- dcast (cast), [2](#)
- french_fries, [5](#)
- guess_value, [3](#)
- melt, [3](#), [4](#), [6](#), [10](#)
- melt.array, [6](#), [7](#), [9](#), [10](#)
- melt.data.frame, [6](#), [8](#), [8](#), [10](#)
- melt.default, [8](#), [9](#), [9](#), [10](#)
- melt.list, [6](#), [8–10](#), [10](#)
- melt.matrix (melt.array), [7](#)
- melt.table (melt.array), [7](#)
- melt_check, [11](#)
- parse_formula, [11](#)
- recast, [12](#)
- smiths, [13](#)
- tips, [13](#)
- type.convert, [5](#), [8](#)